

# ISO MARSIGLIA

## Natural protective agent in paste

### DESCRIPTION

Iso Marsiglia Isocolor<sup>®</sup> it is a natural matt water-based protective agent, anti-dirt and eco-friendly.

It is suitable for the protection and maintenance of surfaces realized with Iso Classic Isocolor<sup>®</sup>, Iso Classic Superlucido Isocolor<sup>®</sup>, Iso Botticino Isocolor<sup>®</sup>, Iso Decor Isocolor<sup>®</sup> and generally for all supports treated with antique and lime-based stucco, such as stucco and marmorino.

It is composed by pure Marseilles vegetable soap and special additives.

### FIELDS OF EMPLOYMENT

Iso Marsiglia Isocolor<sup>®</sup> is applicable on all lime-based finishes.

### CHARACTERISTICS AND ADVANTAGES

Iso Marsiglia Isocolor<sup>®</sup>:

- enhances the shine of the finishes;
- protects the surface without altering its breathability;
- is ready to use and easy to apply.

### HOW TO USE

The application temperature must be between 10 and 30 ° C and the relative humidity must be less than 85% even within 24 hours after application. The substrate must be dry.

The product is ready to use.

Apply Iso Marsiglia Isocolor<sup>®</sup> with a steel spatula several successive times, wet on wet, until completely absorbed. It has to be smooth troweled very well. Then polish with a soft dry cloth (TNT, microfiber, cotton) removing any soap powder.

### TECHNICAL CHARACTERISTICS

Pack	2 kg
Dilution	Ready to use
Specific weight	0,82 ± 0,02 kg/l
Theoretical yield (consumption)	0,03 ÷ 0,06 Kg/m <sup>2</sup> (40-60 mq/lt)

Isocolor s.r.l. via Alcide de Gasperi 53, 31010 Maser (TV) ITALY T. +39 (0)423.565138 P.IVA: 04295200267

---

Dry in depth	48 hours with temperature at 20°C
pH	0 ± 1
Water vapor permeability (Sd)	High 0,06m (Reference standard: UNI EN ISO 7783-2:2001)
VOC According to Dir. 2004/42/CE - Cat. A/I Limit Value 2010: 200 g/Lt	0,011 g/Lt

### STORAGE AND SAFETY

Iso Marsiglia Isocolor<sup>®</sup> can be stored for at least 12 months in the original sealed containers and kept in a cool, dry place at temperatures between 5 and 30°C.  
The product can not stand in frost.  
Consult the safety data sheet before use.

#### IMPORTANT

This product is formulated to be used as in the application above. The addition of any other product compromises the final result of the surface.

All information contained in this sheet is based on the best practical and laboratory experiences. It is the customer's responsibility to verify that the product is suitable for the intended use. The manufacturer declines all responsibility for the results of incorrect applications. It is advisable to always carry out tests on small surfaces before application. Data can be changed at any time. This sheet replaces and cancels previous ones.

It is essential that also the technical and safety data sheets of the other products mentioned in this technical data sheet are consulted.  
Product intended for professional use.